




ARIZONA ARCTIC

911217



Soft PVC hose with rigid PVC spiral, suitable for use in particularly cold climates, for delivery and suction of liquids. Also available in the antistatic version (BY REQUEST: code 911243).

DETAILS

 SMOOTH SURFACE *****

 FLEXIBILITY *****

 ABRASION RESISTANCE *****

 TEMPERATURE RANGE -40 °C 45 °C

 CHEMICAL RESISTANCE PVC OIL Table

 CRUSHING RESISTANCE *****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H ₂ O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
51	2	50.8	61.8	3	9	9	165	5.5	4.8	9	right	1100	30	On demand
63	2 1/2	63.5	75.5	3	9	9	205	6	5.3	11	right	1450	30	On demand
76	3	76.2	89.2	3	9	9	260	6.5	6	11.5	right	1800	30	On demand
80		80	94	3	9	9	280	7	6.5	10.5	right	1900	30	On demand
89	3 1/2	89	103	2.5	9	7.5	300	7	6.5	11.8	right	2250	30	On demand
102	4	101.6	117	2	9	6	330	7.7	6.7	13	right	2800	30	On demand
110		110	126.4	1.5	9	4.5	360	8.2	7.2	11.5	right	3400	20	On demand
127	5	127	144	1	9	3	420	8.5	7.8	14	right	4000	20	On demand
152	6	152.4	170	1	9	3	510	8.8	8.5	15	right	5000	20	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)